

KEY FEATURES

- 20ft/6m a minute
- · Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel
- 1"/25mm mounting thickness
- Heavy duty construction

GREAT FOR USE IN

- Sign makers
- · Print finishers
- · Vehicle Graphic Production
- · Traffic and Safety Divisions

IDEAL WHEN LAMINATING

- · Posters, graphics and signs
- · Mounted prints to board
- Pop-up displays
- Vinyls, tapes, films and pre-masks
- Outdoor signage and more...

Easymount® is designed to perform and built to last.



Easymount®laminators are designed to perform and built to last with advanced features allowing for easy lamination, mounting and pre-masking graphics.

Designed in-house by Vivid, the Easymount® range gives businesses increased finishing capabilities to offer-eliminating the need for outsourcing.

- Solid heavy duty construction
- Release liner take-up
- 1"/25mm adjustable rollers
- · Large rollers for even pressure
- Intelligent reverse mechanism
- Foot pedal for controlled operation

Specifications	EM-1400SH	EM-1600SH	EM-1400C	EM-1600C
Laminating Speed (m/ft/min)	6m/20ft	6m/20ft	6m/20ft	6m/20ft
Max. Width (mm/inches)	1400mm/55"	1600mm/63"	1400mm/55"	1600mm/63"
Mounting Thickness (mm/inches)	25mm/ 1"	25mm/1"	25mm/1"	25mm/ 1"
Roller Diameter (mm/inches)	112mm/4"	130mm/5"	112mm/4"	130mm/5"
Laminating Temperature (°C/°F)	0-60°C/32-140°F	0-60°C/32-140°F	(ex	-
Control Panel	Digital	Digital	Digital	Digital
Pressure Adjustment	Manual/Gauge	Manual/Gauge	Manual/Gauge	Manual/Gauge
Film Core (mm/inches)	77mm/3"	77mm/3"	77mm/3"	77mm/3"
Power Supply AC (V–Hz)	110 - 60	110 - 60	110 - 60	110 - 60
Power Consumption (W)	1300	1500	50	50
Overall Dimensions (mm/inches)	1990x650x1255mm/ 78x26x49"	2190x650x1255mm/ 86x26x49"	1990x650x1255mm/ 78x26x49"	2190x650x1255mm/ 86x26x49"
Gross Machine Weight (Kg/lbs)	210Kg/462lbs	245Kg/540lbs	210Kg/462lbs	245Kg/540lbs
Warranty	1 year	1 year	1 year	1 year

Additional sizes: EM-1200 & EM-2100. In both single hot and cold options

^{*}For full terms & conditions on parts and labor warranty, contact sales@rockhilldist.com