

easymount[®]

SIGN

WIDE FORMAT LAMINATING SYSTEM

KEY FEATURES

- Up to 16ft/5m a minute
- 1"/25mm mounting thickness
- Variable speed control
- Integral media take-up unit
- Self-gripping mandrels
- Magic eye safety feature
- Heated top roller
- Large roll diameter
- Single lift mechanism
- Heavy duty construction
- Release liner take-up
- Simple reverse mechanism
- Foot pedal

IDEAL SOLUTION FOR

- Sign makers
- Print finishers
- Vehicle Graphic Production
- Traffic and Safety Divisions
- Pre-Masking
- Photo and Graphic Mounting

IDEAL FOR LAMINATING

- Single banners
- Roll-to-Reel graphics
- Posters, graphics and signs
- Mounted prints to boards
- Pop-up displays
- Vinyls, tapes, films and pre-masks
- Outdoor signage and more...

Easymount Sign Single Hot[®] is designed to perform and built to last.



▲ EM-S1600H

Design & Performance

This Easymount[®] Sign laminator is designed to perform and built to last, with its solid heavy duty construction.

An easy-to-use laminating system with self gripping mandrels and a flip down feed tray.

The Easymount[®] Sign includes an integral media take-up unit, making the system ideal for single sheeted graphics or roll-to-reel laminating up to 165ft.

INCLUDES

- INTEGRAL MEDIA TAKE-UP UNIT
- SELF GRIPPING MANDRELS
- SINGLE LIFT MECHANISM

Specifications

	EM-S1400H	EM-S1600H
Laminating Speed (m/ft/min)	up to 5m/16ft	up to 5m/16ft
Max. Width (mm/inches)	1420mm/56"	1620mm/64"
Mounting Thickness (mm/inches)	25mm/1"	25mm/1"
Top Roller Diameter (mm/inches)	130mm/5"	130mm/5"
Laminating Temperature (°C/°F)	45°C/113°F - can be switched off	45°C/113°F - can be switched off
Pressure Adjustment	Manual	Manual
Film Core (mm/inches)	77mm/3"	77mm/3"
Power Supply AC (V-Hz)	110 - 60	110 - 60
Power Consumption (W)	1000	1200
Overall Dimensions (mm/inches)	1846x550x1365mm/73x22x54"	2046x550x1365mm/81x22x54"
Gross Machine Weight (Kg/lbs)	136Kg/300lbs	156Kg/344lbs
Gross Stand Weight (Kg/lbs)	25Kg/55lbs	30Kg/66lbs
Warranty*	1 year	1 year

*For full terms & conditions on parts and labor warranty, contact sales@rockhilldist.com